

TB 125 - Flat Bar

Flat Termination Bar



Description

TB 125 is a flat termination bar used at top of flashing to secure it to the backup. TB 125 is compatible with all flashings.

Uses


TB 125 Termination Bar is used for edge or vertical parapet wall terminations.

Dimensions

- .125" x 1" x 8' long
- 1/4" holes spaced 8" on center

Finishes

- Type 304 Stainless Steel
- Aluminum



Packaging

Properties

Description	Measurement	
Material	Type 304 Stainless Steel	Aluminum
Dimensions	.125" x 1" x 10' long	.125" x 1" x 8' long
*Holes	1/4" holes (8" on center)	1/4" holes (8" on center)
Packaged	100 ft per bundle	200 ft per bundle

Type 304 Stainless Steel
.125" x 1" x 10' long
100 ft per bundle

Aluminum
.125" x 1" x 8' long
200 ft per bundle

**If required, holes can be drilled to fit custom lengths. Please call a Barrett technical representative for all inquiries or to place a custom order.*

LIMITED WARRANTY: Barrett warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Barrett makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to The Barrett Company, LLC. Barrett to replace or to refund the purchase price of the quantity of Barrett proven to be defective, and Barrett shall not be liable for any loss or damage.

20.1
Document: KF-01053



800 | 647 | 0100
F 908 | 647 | 0278