



Between the World
and The Weather
Since 1928

BARRETT RAM COLDTAR (COLD PROCESS) PRIMARY PRODUCT LIST

Product Data Sheets, specifications and Safety Data Sheets are available on our website barrettroofs.com or by calling Barrett Technical services at 800-647-0100

Bitumen Adhesives

Ram ColdTar®

Uniquely combines asphalt, coal tar and SBS rubber polymers, creating a highly elastomeric adhesive and thermoplastic waterproofing membrane.

Ram ColdTar® Plus

An exclusive SBS thermoplastic rubber coating compound, designed for waterproofing existing roofing bitumens and aggregate surfaces. Ram cold Tar creates a new high performance membrane that utilizes an existing membrane's thickness and mass creating a new monolithic, elastomeric membrane that is resistant to ponded water and other elements detrimental to the life of the weatherproofing membrane.

Reinforcement and Flashing Material

Ram 40

A trilaminate polyester and fiberglass reinforcement sheet, impregnated and coated with asphalt.

Poly-Felt 125 VP

Spunbond, heat resistant polyester reinforcement that is "sandwiched" between two thick layers of Ram-Tough 250 membrane and other bituminous materials.

Poly-Felt 155 CP

A lightweight spunbond polyester reinforcement fabric (no asphaltic coating) for cold process only.

Ram 306

An SBS polymer modified-bitumen membrane with a ceramic granule surface. 4mm thick. Also used as a finished cap sheet. (ASTM D-6164, Type 1, Grade G).

Finish Options

Ram 309 FR

Fire rated, fiberglass reinforced, granule surfaced, 2.3mm (90.5 mils) thick, generally used as a cap sheet. (ASTM D-6163, Type II, Grade G)

Ram Ultra White Coating

White acrylic latex-polymer water-based emulsion offering excellent reflectivity. Energy Star® approved and available for LEEDS credits. Provides superior UV protection, mildew resistance, color stability, weatherability and flexibility. Requires Ram Ultra-White Primer.

Ram Ultra White Primer

Clear water-based acrylic primer formulated to provide excellent adhesion properties to various surfaces. Specifically designed to be used as a primer coat for Barrett Ultra White acrylic coating.

Ram Ultra Silver Coating

Made with high quality SBS polymer-modified asphalt, premium aluminum flake pigment and refined solvents, Ram Ultra Silver Coating provides very good UV protection and heat reflection. Solvent based, in compliance with EPA regulations of less than 250g/L. (ASTM D-2824, Type I)

Ram Granules

Colored ceramic granules that provide improved weathering resistance and aesthetic appeal. Most commonly used as a lightweight wear surfacing, set in asphaltic compounds and adhesives.

Ram Ultra White Cap Sheet

A multi-purpose SBS polymer-modified, polyester reinforced asphalt membrane sanded on the underside and a highly reflective white reinforcement film on the top surface. The composite membrane provides elongation, elasticity, flexibility, tensile strength, toughness and reflectivity. LEED accepted and Energy Star Approved.

Accessories / Miscellaneous

Ram Mastic

Cold-applied, trowel grade, high performance SBS rubberized mastic for miscellaneous repair. (Meets or exceeds D-4586 Type I).

Ram A.R.C.

Trowel grade flashing cement. (Meets or exceeds ASTM D-4586 Type I).

Ram Primer/Surface Conditioner

Asphalt based primer. Meets or exceeds ASTM D-41 minimum standards.

Roof Release Agent

Ready-to-use, "parting agent" bond breaker which works with all types of bitumen and asphalt, to resist adhesion and build up on shoes, wheels and tools, making clean-up easier. Its advanced formula is environmentally safe, biodegradable and non-toxic and comes in consumer sized spray cans.

Ram Caulk

Ready-to-use, low modulus, non-sag silicone for sealing joints in concrete, masonry, wood and sheet metal in all climates. (Meets or exceeds ASTM D-5893 Type NS Sealant)

For specialty or custom blended products not shown here contact Barrett Technical Services.

* All Barrett products comply with all EPA and OSHA regulations in effect as of June 1, 2016