



Between the World
and The Weather
Since 1928

Safety Data Sheet

1: IDENTIFICATION AND EMERGENCY INFORMATION

PRODUCT NAME: BLACK PEARL PRIMER-ADHESIVE

MANUFACTURER NAME: Barrett Company, Inc.
33 Stone House Road
Millington, New Jersey 07946


CHEMTREC EMERGENCY PHONE: 800-424-9300
INFORMATION PHONE: 908-647-0100
DATE PREPARED: January 21, 2014

Recommended Use: A fluid applied waterproofing primer and adhesive used in conjunction with Black Pearl Sheet Membrane.

Restrictions on Use: For professional contractor use only.

2: HAZARDS IDENTIFICATION

HAZARD RATING
4 – SEVERE
3 – SERIOUS
2 – MODERATE
1 – SLIGHT
0 - MINIMAL



NFPA 704: Health: 2 Flammability: 3 Instability: 0
HMIS III: Health: 2 Flammability: 3 Physical Hazard: 0

Emergency Overview:

WARNING! Flammable liquid and vapor. May affect the central nervous system causing dizziness, headache or nausea. May be harmful if inhaled or swallowed. Prolonged or repeated contact may dry the skin and cause irritation and burns.

Vapors are heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Potential Health Effects:

- Inhalation:** Vapors and fumes from can be unpleasant and may cause nausea, headache, and respiratory irritation. Hydrogen sulfide (H₂S) gas can be present in the vapor.
- Ingestion:** Swallowing large amounts of this material may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.
- Skin Contact:** Contact with unheated material may cause irritation or drying.
- Eye Contact:** Contact with unheated material may cause irritation.

R10: Flammable
R36/37/38: Irritating to eyes, respiratory system and skin
S16: Keep away from all sources of ignition – No Smoking
S23: Do not breathe fumes/vapors
S36/39: Wear suitable protective clothing and eye/face protection.

3:**COMPOSITION AND INFORMATION ON INGREDIENTS**

COMPONENT	CAS#	% WEIGHT
Asphalt	8052-42-4	40-75
Solvent Naphtha (Petroleum), Light Aliphatic Distillates	64742-89-8	10-40
Aliphatic Hydrocarbons (Stoddard)	8052-41-3	0-10
Attapulgate Clay	8031-18-3	1-10
Cellulose Fiber	9004-34-6	1-10
Surfactant	28701-67-9	0-1
Polymer – Trade Secrecy Registry No. NJTSRN-13-5		1-10

4:**FIRST AID MEASURES****Inhalation:**

If breathing difficulties, dizziness, or lightheadedness occur when working in areas with vapor concentration, victim should seek air free of vapors. If victim experiences continued breathing difficulties, administer oxygen until medical assistance can be rendered. If breathing stops, begin artificial respiration and seek immediate medical attention.

Skin Contact:

If this product comes in contact with skin, remove material with mineral oil or vegetable oil, then wash with soap and plenty of water. Get medical attention if irritation from contact persists. Skin contact with clothing saturated with solvent can cause severe burns. Contaminated clothing should be removed immediately and excess material wiped from the skin.

Eye Contact:

If this product comes in contact with the eyes, flush with plenty of water for at least 15 minutes and seek medical attention.

Ingestion:

If this product is swallowed, **DO NOT INDUCE VOMITING.** Seek immediate medical attention. **NOTE TO PHYSICIAN:** Perform gastric lavage in accordance with procedure for ingestion of petroleum products.

5:**FIRE FIGHTING MEASURES****Flammable liquid and vapor.**

Flash Point (TCC): 50°F Min.

Explosive Limits: LEL = 0.9% UEL = N.E.

Extinguishing Media:

Use foam, carbon dioxide (CO₂), or dry chemical. Water may be used to cool containers exposed to heat.

Unusual Fire & Explosion Hazards:

Above flash point, material will release flammable vapors which can burn or be explosive in confined spaces if ignited. Do not mix with strong oxidants such as liquid chlorine or concentrated oxygen.

Fire-Fighting Instructions:

Vapors are heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger. Minimize breathing vapors, gases or fumes of decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces.

6: ACCIDENTAL RELEASE MEASURES

Take proper precautions to ensure your own health and safety before attempting spill control or clean-up. Do not touch or walk through spilled material.

Shut off leaks if possible without personal risks. Eliminate sources of ignition. Add sand, earth, or other suitable absorbent to spill area. Transfer to suitable containers. Avoid sparks or hot metal surfaces.

Keep product out of sewers and waterways by diking or impounding. Advise authorities if product has entered or may enter sewers or waterways. Assure conformity with applicable government regulations.

7: HANDLING AND STORAGE

Toxic quantities of hydrogen sulfide (H₂S) may be present in vessels which contain or have contained this material. Persons opening or entering these compartments should first determine if H₂S is present. See Protective Equipment section. **DO NOT ATTEMPT RESCUE WITHOUT WEARING APPROVED SUPPLIED-AIR OR self-contained breathing equipment.**

Vapors are heavier than air and may travel along the ground or be moved by ventilation to locations distant from the point of material handling. To prevent ignition, avoid smoking, keep away from heat, open flames, and sources of static or electrical sparking. Use explosion proof motors and equipment. Tank trucks or other containers should be grounded and/or bonded when the material is transferred.

Use with adequate ventilation. Avoid open flames. Minimize breathing vapor, mist, and fumes. Avoid prolonged and repeated contact with skin. Adhere to good hygienic practices. Prevent contact with food and tobacco products. Do NOT take internally. Never siphon by mouth.

Health studies have shown that many petroleum hydrocarbons pose potential human health risks which vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

Store in a cool, dry place, out of the sun and away from heat, sparks and open flames.

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Provide ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the exposure limits indicated below. All electrical equipment should comply with the National Electrical Code. An emergency eye wash station and safety shower should be located near the work-station.

Exposure Guidelines:

Hazardous Components	CAS #	OSHA PEL: TWA	OSHA TLV: TWA
Asphalt	8052-42-4	N.E.	.5mg/m ³
Solvent Naphtha (Petroleum), Light Aliphatic Distillates	64742-89-8	300 ppm	300 ppm
Aliphatic Hydrocarbons (Stoddard)	8052-41-3	500 ppm	100 ppm
Surfactant	28701-67-9	N.E.	N.E.

N.E. = Not Established

OSHA = Occupational Safety and Health Administration

ACGIH = American Conference of Governmental Industrial Hygiene

PEL = Permissible Exposure Limits

TWA = Time Weighted Average

TLV = Threshold Limit Value

Respiratory Protection:

Use supplied-air respirator in confined areas or when vapors exceed exposure guidelines.

Eye Protection:

Safety glasses or face shield for liquid and/or hot material.

Protective Gloves:

Solvent impervious gloves.

Other Protective Clothing Equipment:

Long sleeves and impervious clothing to protect from splashing.

Work/Hygienic Practices:

See Section 7.

9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor:	Brown to Black viscous liquid, petroleum odor
Vapor Pressure (mm Hg @ 20°C Volatiles) :	>5
Boiling Point °F Volatiles:	240-300°
Evaporation Rate (Butyl Acetate = 1) @ 77°F:	N.D.
Melting Point °F (Ring & Ball):	N/A
Vapor Density (Air=1) @ 20°C Volatiles:	>3.5
Solubility in water:	Insoluble
Flash Point °F (Closed Cup):	50°F Min.
Specific Gravity (H₂O = 1):	N.D.

10: STABILITY AND REACTIVITY

Stability:
Stable

Conditions to avoid:
Keep away from heat, sparks, open flames and strong oxidizing agents. Auto-ignition temperature unknown

Incompatible Materials:
Strong acids, alkalies, and oxidizers.

Hazardous Decomposition or Byproducts:
Combustion: carbon dioxide (CO₂), carbon monoxide (CO), sulfur oxides (SO_x), nitrogen oxides (NO_x), hydrogen sulfide (H₂S), smoke, fumes and/or unburned hydrocarbons.

Hazardous Polymerization:
Not expected to occur.

11: TOXICOLOGICAL INFORMATION

Product may cause respiratory irritation, headache, dizziness, nausea and vomiting. Prolonged or repeated contact with skin may cause dermatitis.

Carcinogenicity: NTP: No IARC Monograph: No OSHA Regulated: No

ADDITIONS HEALTH DATA:**ASPHALT:**

No association has been established between industrial exposure to petroleum asphalt and cancer in humans. The International Agency for Research on Cancer (IARC) has recently reviewed the carcinogenic potential of asphalts. They concluded that there was insufficient evidence that undiluted, air-refined asphalt was carcinogenic to animals, while there was only limited evidence that steam-refined asphalts were carcinogenic to animals. The asphalt cement used in this product is straight-run asphalt cement, not steam-refined or oxidized asphalt. Additionally, there was insufficient evidence to conclude that asphalts were carcinogenic to human beings. Studies in which mice were exposed to a variety of whole asphalts did not result in any increased cancer rate; mice exposed to asphalts diluted with hydrocarbon solvents had increased incidence of certain types of cancer. Brief or intermittent skin contact with this asphalt product is not expected to produce any serious effects. While normal handling of this product is not likely to cause cancer in humans, skin contact and breathing of mists, fumes, or vapors should be reduced to a minimum. We strongly recommend that the precautions outlined in this SDS be followed when handling this material.

SOLVENT:

Hydrocarbon solvents derived from petroleum may cause irritation when in contact with eyes and skin. Prolonged or repeated contact with skin can cause dermatitis. Systemic effects of these solvents are respiratory tract irritation, central nervous system depression (narcosis) in high concentration, nausea, vomiting, and possible damage to liver and kidneys. No known studies have associated these solvents with carcinogenic activity.

12: ECOLOGICAL INFORMATION

EPA Hazard Classification Code:

Acute Hazard: _____ Chronic Hazard: _____ Fire Hazard: _____ Pressure Hazard: _____

Reactive Hazard: _____ Not Applicable: X

13: DISPOSAL CONSIDERATIONS

Material Disposal Instructions:

Recover or recycle if possible. Recovered non-usable material may be regulated by US EPA as a hazardous waste due to its ignitibility.

Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed to contaminate soil or water. Dispose of in accordance with local, state and federal regulations.

Container Disposal Instructions:

Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Refer to Section 7 before handling the product or containers. Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums. Send to a drum or metal recycler.

14: TRANSPORT INFORMATION

The descriptions shown may not apply to all shipping situations. Consult 49 CFR, or appropriate regulations, for additional description requirements.

DOT Shipping Name: Asphalt Adhesive
DOT Label Information: Flammable liquid
DOT Hazard Class: 3
DOT ID Number: UN-1999
DOT Packing Group: II

15: REGULATORY INFORMATION

SARA TITLE III- EPA Regulation 40 CFR 302 (CERCLA Section 102); CFR 355 (SARA Section 301-304); CFR 372 (SARA Section 311-313)

This product contains the following chemicals subject to the reporting requirements of SARA 313 and 40 CFR 372:

	CAS NUMBER	WEIGHT %	REPORTABLE QUANTITY
Xylene	1330-20-7	< .1	100 lbs.
Ethyl Benzene	100-41-4	< .02	1,000 lbs.
Benzene	71-43-2	< .01	10 lbs.

EPA HAZARD CLASSIFICATION: Acute Hazard/Chronic Hazard/Fire Hazard/Pressure Hazard/Reactive Hazard:
 Fire Hazard, Acute Health Hazard

GOVERNMENTAL INVENTORIES: All components are listed in the U.S. TOSCA, Canadian DSL, Australian AICS, European EINECS, Korean KECI, and Philippines PICCS Inventories.

Some asphalt contains sulfur compounds which may form hydrogen sulfide (H₂S) when heated. The rotten eggs odor of H₂S is unreliable as an indicator of concentration because it may be entirely masked by the odor of the asphalt. Signs and symptoms of overexposure to H₂S include respiratory tract irritation, headaches, dizziness, nausea, gastrointestinal disturbance, coughing, a sensation of dryness and pain in the nose, throat and chest, confusion and unconsciousness. H₂S concentrations of 700-1000 ppm can be extremely hazardous or fatal.

NFPA 704 Rating (Health, Flammability, Instability): 2, 3, 0

HMIS III Rating (Health, Flammability, Physical Hazard): 2, 3, 0

Date of Issue: January 21, 2014

Revision Statement:

This Safety Data sheet has been revised to change the shipping DOT ID number and label information to better reflect the requirements of the transport carriers.

Supersedes: May 21, 2013

Disclaimer: The information and recommendations contained herein are to the best of Barrett Company's knowledge and belief, accurate and reliable as of the date issued. Barrett Company does not warrant or guarantee their accuracy or reliability, and Barrett Company shall not be liable for any loss or damage arising out of the use thereof. The information and recommendations are offered for the users' consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. It is also the users' responsibility to make certain that it is relying upon the most recent, updated, information and recommendations available from Barrett Company. The Environmental Information included above as well as the Hazardous Material Identification System (HMIS) and National Fire Protection Association (NFPA) ratings have been included by Barrett Company in order to provide additional health and hazard classification information. The ratings recommended are based upon the criteria supplied by the developers of these rating systems, together with Barrett Company's interpretation of the available data. We make no warranty as to the results to be obtained in using any material and, since conditions and methods of use are not under our control, we must necessarily disclaim all warranties of merchantability or fitness for any particular use as well as all liability resulting directly or indirectly from the use of any materials supplied by us.