

ram 400 PS

PRODUCT DESCRIPTION

ram 400 PS is a self-adhering preformed rubberized asphalt sheet that is reinforced with a heavy polyester fabric. Utilizing Kraton® SBS rubber polymers and select asphalt, the **ram** 400 PS waterproofing sheet has a smooth tacky adhesive surface on both sides with plastic film release sheet.

ram 400 PS is puncture resistant, flexible at low temperatures and self healing at warmer temperatures.

USES

Typically used in conjunction with vertical **ram-Tough** Waterproofing Systems, **ram** 400 PS provides an excellent means of "belting" and protecting **ram-Tough** 250 when waterproofing vertical walls and difficult flashing conditions. It is compatible with **ram-Tough** 250 Waterproofing, **ram** Mastic and most asphaltic membranes.

Packaging

Roll Size	39.5 inches x 50 feet (164 ft ₂ , gross)
Weight	50 pounds per roll (150 ft ₂ , net)

Physical Properties

Thickness	1.5 mm (60 mils)	
Reinforcement	polyester, 170 grams m ₂	
Polymer Modifier	Kraton® SBS (styrene-butadiene-styrene)	
Release Backing	silicone coated polyethylene	
Breaking Strength	ASTM-D-412	50 pounds per inch
Elongation	ASTM-D-412	25%
Puncture Resistance	ASTM-E-154	80 lbs.
Cold Bend	ASTM-D-146	-15 °F

Barrett hopes the information given here will be helpful. It is based on our best knowledge and is believed to be true and accurate. Properties given are typical values and are not specifications unless otherwise stated. We assume no responsibility for the use of these statements, recommendations or suggestions, nor do we intend them as a recommendation for any use not expressly stated herein.