



Between the World
and The Weather
Since 1928

Barrett Ram-Tough 250 Advantages

Rubberized asphalt membrane for waterproofing and roofing which uniquely offers:

1. Tenacious bond to substrate, no below membrane water migration.
2. Triple protection at critical flashing points.
3. Ease of detailing, follows contour and irregularities, no cutting and piecing.
4. Self-healing above 60°F.
5. Installation at 0°F.
6. Extra thick: 215 mils minimum thickness provides more mass, more protection from construction abuse and a better seal of developing cracks.
7. Thermoplastic rubberized membrane requires no curing
 - Fast, ready for other trades immediately.
 - Tolerates adverse weather immediately after installation.
 - Easy to find and patch construction damage.
 - Homogenous day-to-day laps.
 - Easy to flash in subsequent details.
8. 100% solids, no solvent fumes, installed thickness is the finished thickness.
9. Monolithic, one step, no seams, no mixing, no curing failures.
10. Only approved and trained applicators install warranted systems.
11. Unbeatable track record, references, key projects.
12. Energy saving extruded polystyrene insulation can be used with **Ram-Tough Systems** at economical cost.

BARRETT COMPANY · 33 Stone House Road · Millington, NJ 07946
Phone: 800-647-0100 · Fax: 908-647-0278 · E-Mail: technicalservice@barrettroofs.com
www.barrettroofs.com