

Ram 309 FR (High Tensile)

PRODUCT DESCRIPTION

Ram 309 FR is a high tensile SBS Polymer-Modified Bitumen membrane with fiberglass reinforcement and embedded mineral granule surface. It is designed for hot mop applications.

Ram 309 FR is available with a fire retardant formulation.

USES

With **Ram-Tough** BUR and **Ram-Tough** Waterproofing Systems, for all weather-exposed flashings, including wall flashings. Also used as a cap sheet with asphalt built-up roofs. The sheet material has excellent adaptability to extreme temperature ranges, excellent UV resistance, good chemical resistance and is 100% compatible with **Ram-Tough** modified bitumens.

Packaging

Roll Size	33 feet x 39 inches (one square)
Weight	95 pounds per roll

Performance

Thickness	4 mm	
Surfacing	ceramic granules	
Reinforcement	fiberglass mat	
Polymer Modifier	Shell Kraton® SBS Polymers	
Elongation	ASTM-D-412	2%
Cold Bend	CGSB-37-GP56M	-20°F

Barrett hopes the information given here will be helpful. It is based on our best knowledge and is believed to be true and accurate. Properties given are typical values and are not specifications unless otherwise stated. We assume no responsibility for the use of these statements, recommendations or suggestions, nor do we intend them as a recommendation for any use not expressly stated herein.