



Between the World
and The Weather
Since 1928

Roof Release Agent

PRODUCT DESCRIPTION

The adhesive properties of polymer-modified bitumen used in elastomeric roofing and waterproofing systems dramatically increases the adhesion of the membrane to the structure, improving resistance to wind damage.

The increased adhesion of the bitumen to rooftop equipment tires and workers shoes is not as desirable.

Specifically designed for versatility, Roof Release Agent acts as a parting agent, reducing bitumen adhesion to tires and shoes while making clean-up easier.

In many ways superior to other available products, this advance formula is environmentally safe, biodegradable, non-toxic and works with all types of bitumen and asphalt preventing adhesion and build-up on shoes, wheels and tools.

FEATURES

- Biodegradable
- Non-Toxic
- Low Combustibility
- Non-Hazardous
- Non-Corrosive
- No Offensive Odor
- Free of Phenols, Phosphates and Heavy Metals
- Increase Roof Top Safety
- Reduces Strain on Worker Legs and Knees
- Increased Productivity of Workers

Roof Release Agent was tested safe on:

- Aluminum
- Titanium
- Stainless Steel
- Copper
- Concrete
- Cadmium
- Galvanized Steel
- Brass
- Nickel
- Rubber

APPLICATION INSTRUCTIONS

Roof Release Agent is ready-to-use and can be sprayed directly on tools, equipment, tires and soles of shoes. Shake before using. Allow spray application to sit on treated surface for 1 to 3 minutes before resuming work.

Since this product functions as a parting agent, do not spray over unfinished roof membrane as it may affect proper adhesion of membrane components.



CLEAN-UP

For equipment clean-up, Roof Release Agent can be safely flushed with water, which forms a non-toxic, fully dispersible emulsion.

STORAGE

Do not store in temperatures above 120°F (49° C) as container may burst.

PACKAGING

32 oz.(.907 kg) plastic pump spray bottle (6 bottles per case)

PRODUCT SAFETY INFORMATION

Roof Release Agent is non-toxic, non-hazardous and biodegradable. As with the use of any chemical product, the user should review the Material Safety Data Sheet for the appropriate health and safety warnings before use.

- Eyes: Flush eyes with large amounts of water. If irritation persists, seek medical assistance.
- Ingestion: Do not induce vomiting. Seek medical assistance immediately.
- Skin: Avoid prolonged or repeated skin contact as it may cause skin to dry out. Wash area thoroughly with soap and water after handling.

Spill Response: Flush with water. Mop up remaining liquid and dispose of in accordance with federal, state and local regulations.

The user should not assume that all safety measures are indicated or that other measures may not be required.

Issued 6/10/13